


www.rhinocuttingmat.co.uk

SUPALITE

Product Specification Details





100% Recyclable



Our SupaLite clear cutting mats offer great durability, good self-healing properties and provides a perfect cutting surface or simply as a workbench surface protection mat. SupaLite cutting mats are completely clear with a very slight blue tint...

- 3mm Thick & double-sided for twice the life. Ideal for light to medium use cutting applications or great as an unobtrusive workbench protector
- A great investment for your workplace protects your work surface, and with great hygienic 'easy clean' and waterproof properties, means you can keep your bench looking fantastic.
- Suitable for all types of applications including Flat-Bed Laminator/Roller Tables to protect the glass bed including the Rollover, RollsRoller, Bubble-Free, CWT, Kala, Rapid Applicator, RiteRoller, V Roller, Mounters Mate Smart Station and Mounters Mate Workstation Pro-Series

Product Applications

- ✓ Medium duty workbench and work surface protection
- ✓ Print and graphics trimming
- ✓ Flat-bed laminator/applicator tables
- ✓ Multi-purpose cutting, light crafting and hobby work
- ☐ General warehouse use and worktop protection





Product Advantages

Up to **75%** Increase in life expectancy over previous surface solutions

Up to 65% Increase in speed and precision of cutting and trimming

Up to **68%** improvement in preserving existing work surfaces, protecting products you're working on, and avoiding cross-contamination

Up to 50% Reduction in replacement tool costs by extending tool and blade life

Up to **50%** improvement for ease of spill clean up, reducing liquid absorption, and keeping workspaces clean

Precision, Protect, Prevent.

Product Maintenance and After-Care

- Use a light touch when using a knife on your cutting mat especially when using a heavy duty knife or cutter.
- Clean with a light soapy water solution
- Your mat is likely to be delivered rolled up, so please unroll as soon as possible and lay flat. it may take 24-48 hours to lay completely flat due to the nature of the material. Ideally store flat after initial unrolling.
- Once the first side is totally worn, the reverse can be used.

Material Properties

This material has a low friction coefficient, and good electrical and abrasion resistance. It is a non-hygroscopic material with good electrical properties it also makes it suitable in a variety of electrical insulation applications.

- ☑ Solvent proof and resistant to most chemicals
- ✓ Waterproof
- ☑ Light transmission to 75%
- ☑ Free of phthalate plasticisers and REACH Conformable







