

www.rhinocuttingmat.co.uk

SUPASEAL

Product Specification Details



	Wear Rating	Self-Healing Rating	ECO Scale
Α			
В			
C			
D			
Ē			

100% Recyclable



Our SupaSeal clear cutting mats offer long term durability and exceptional self-healing properties and provide a perfect cutting surface or simply as a workbench surface protection mat. SupaSeal cutting mats are completely clear with a very slight blue tint.

- 5mm Thick & double-sided for twice the life. Ideal for Medium to Heavy duty cutting applications or a tough workbench protection mat
- A great investment for your workplace protects your work surface, and with great hygienic 'easy clean' and waterproof properties, means you can keep your bench looking fantastic.
- Suitable for all types of applications including Flat-Bed Laminator/Roller Tables to protect the glass bed including the Rollover, RollsRoller, Bubble-Free, CWT, Kala, Rapid Applicator, RiteRoller, V Roller, Mounters Mate Smart Station and Mounters Mate Workstation Pro-Series

Product Applications

- ☑ Workbench and work surface protection
- ✓ Print and graphics trimming
- ✓ Flat-bed laminator/applicator tables
- ☑ Multi-purpose cutting, light crafting and hobby work
- ☐ General warehouse use and worktop protection





Product Advantages

Up to 75% Increase in life expectancy over previous surface solutions

Up to 65% Increase in speed and precision of cutting and trimming

Up to **68%** improvement in preserving existing work surfaces, protecting products you're working on, and avoiding cross-contamination

Up to 50% Reduction in replacement tool costs by extending tool and blade life

Up to **50%** improvement for ease of spill clean up, reducing liquid absorption, and keeping workspaces clean

Precision, Protect, Prevent.

Product Maintenance and After-Care

- Use a light touch when using a knife on your cutting mat especially when using a heavy duty knife or cutter.
- Clean with a light soapy water solution
- Your mat is likely to be delivered rolled up, so please unroll as soon as possible and lay flat. it may take 24-48 hours to lay completely flat due to the nature of the material. Ideally store flat after initial unrolling.
- Once the first side is totally worn, the reverse can be used.

Material Properties

This material has a low friction coefficient, and good electrical and abrasion resistance. It is a non-hygroscopic material with good electrical properties it also makes it suitable in a variety of electrical insulation applications.

- ☑ Solvent proof and resistant to most chemicals
- ✓ Waterproof
- ☑ Light transmission to 75%
- ☑ Free of phthalate plasticisers and REACH Conformable







