

SUPALITE WHITE

Product Specification Details



	Wear Rating	Self-Healing Rating	ECO Scale 
A			
B			
C			
D			
E			

* Based on average medium duty usage with a standard knife or tooling. The ECO Scale is based on how recyclable the finished product is, or whether the Mat is manufactured using Recycled materials

100%
Recyclable

5 STAR Product
REVIEWS


Our SupaLite White cutting mats offer great durability, good self-healing properties and provides a perfect cutting surface or simply as a workbench surface protection mat. SupaLite White cutting mats dense white.

- 3mm Thick & double-sided for twice the life. Ideal for light to medium use cutting applications or great as a tough workbench protector for education, electronics or Labs.
- A great investment for your workplace – protects your work surface, and with great hygienic 'easy clean' and waterproof properties, means you can keep your bench looking fantastic.

Product Applications

- Medium duty workbench and work surface protection
- Electronics, Education or Laboratories
- Light cutting or Heavy Duty Workbench Protection



www.rhinocuttingmat.co.uk
sales@rhinocuttingmat.co.uk
01280 840293

**THE
CUTTING
EDGE**
OF SURFACE PROTECTION MATS

Product Advantages

Up to **75%** Increase in life expectancy over previous surface solutions

Up to **65%** Increase in speed and precision of cutting and trimming

Up to **68%** improvement in preserving existing work surfaces, protecting products you're working on, and avoiding cross-contamination

Up to **50%** Reduction in replacement tool costs by extending tool and blade life

Up to **50%** improvement for ease of spill clean up, reducing liquid absorption, and keeping workspaces clean

Precision. Protect. Prevent.

Product Maintenance and After-Care

- Use a light touch when using a knife on your cutting mat especially when using a heavy duty knife or cutter.
- Clean with a light soapy water solution
- Your mat is likely to be delivered rolled up, so please unroll as soon as possible and lay flat. it may take 24-48 hours to lay completely flat due to the nature of the material. Ideally store flat after initial unrolling.
- Once the first side is totally worn, the reverse can be used.

Material Properties

This material has a low friction coefficient, and good electrical and abrasion resistance. It is a non-hygroscopic material with good electrical properties it also makes it suitable in a variety of electrical insulation applications.

- Solvent proof and resistant to most chemicals
- Waterproof
- Heat Resistant
- Free of phthalate plasticisers and REACH Conformable

Recycling and REACH Properties

